



Coolant Exchanger CE2000 High Capacity

- Exchange and Backflush Cooling System in less than 10 minutes
- Two line approach allows coolant transfer up to 1 gallon per minute
- Large 7.6 U.S. gallon capacity cylinders
- Quick and easy to use
- Includes heat resistant delrin adapters and tools



Visit www.aecgroup.net for video of the Coolant Exchanger

Coolant Exchanger



2 Tube Model - CE2000 HC

Specifications:

- 7.6 U.S. gallon capacity cylinders
- 8" rigid wheels w/bearing (rear)
- 4" swivel casters with brake (front)
- 8' steel reinforced external hoses

Features:

- Quick and easy hook up
- Two lines, pressure and vacuum, for coolant exchange up to 1 gal. per minute
- Large 7.6 U.S. gallon capacity cylinders
- Easily accessible cylinders for filling
- Balanced, stable design
- CAD designed
- Shut off valve on radiator adapter
- Delrin (non heat conductive) adapters
- Durable, high quality components
- One year limited warranty



Vacuum: 26 Hg (minimum)
 Pressure: Factory set to 10 PSI
 Air requirement: 70 PSI, +/- 6 CFM
 Weight: 125 lbs. (56.7 kgs.)
 Shipping weight: 140 lbs (63.5 kgs.)
 Dimensions Machine:
 23.75" wide (60.3 cm)
 20.25" deep (51.4 cm)
 49.5" high (125.7 cm)